

according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Further trade names

ORAFOL® Langzeitversiegelung für matte Fahrzeugvollverklebungen; UFI: R5JQ-JKFE-JA3W-WVJY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products, Washing and cleaning products. Reserved for industrial and professional use.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	ORAFOL Europe GmbH	
	Germany	
Street:	Orafolstraße 1	
Place:	D-16515 Oranienburg	
Telephone:	+ 49 3301 864 0	Telefax: + 49 3301 864 100
e-mail:	msds@orafol.de	
Internet:	www.orafol.com	
1.4. Emergency telephone	National Poison Information Servi	ice: In case of a medical emergency following
number:	exposure to a chemical, the publi	c should call NHS Direct in England or Wales
	0845 46 47 or NHS 24 in Scotland	d 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Labelling for contents according to regulation (EC) No. 648/2004: < 5% nonionic surfactants, perfumes. Further information: Glykolether, Alcohol.



ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 2 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	-	•	
5131-66-8	3-butoxypropan-2-ol; propylene gly	col monobutyl ether		1 -< 5 %
	225-878-4	603-052-00-8		
	Skin Irrit. 2, Eye Irrit. 2; H315 H319)		
64-17-5	ethanol, ethyl alcohol			1 -< 5 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

Further Information

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. If unconscious place in recovery position and seek medical advice.

After inhalation

Provide fresh air. Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After cleaning apply high-fat content skin care cream.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

@0401.B040030 Do NOT induce vomiting. Get medical advice/attention. Let water be drunken in little sips (dilution effect).

4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: The following symptoms may occur: Headache, Dizziness, Gastrointestinal complaints, Sweating, Drowsiness.

4.3. Indication of any immediate medical attention and special treatment needed

Defoamer (Dimeticon), Water, to which activated charcoal may be added

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. The product itself does not burn.

5.2. Special hazards arising from the substance or mixture

No special fire protection measures are necessary.

5.3. Advice for firefighters

No special fire protection measures are necessary.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire



according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 3 of 10

extinguishing water separately. Do not allow entering drains or surface water. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Avoid: Eye contact

6.2. Environmental precautions

Suitable material for diluting or neutralizing: Water

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid: Eye contact

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

storage temperature: < 30 °C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL



according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 4 of 10

DNEL/DMEL values

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
5131-66-8	3-butoxypropan-2-ol; propylene glycol monobutyl ether			
Worker DNEL	long-term	inhalation	systemic	147 mg/m³
Worker DNEL	, long-term	dermal	systemic	52 mg/kg bw/day
Worker DNEL	, long-term	dermal	local	50 %
Worker DNEL	, acute	dermal	local	50 %
Consumer DN	EL, long-term	inhalation	systemic	43 mg/m³
Consumer DN	EL, long-term	dermal	systemic	22 mg/kg bw/day
Consumer DN	EL, long-term	dermal	local	50 %
Consumer DN	EL, acute	dermal	local	50 %
Consumer DN	EL, long-term	oral	systemic	12,5 mg/kg bw/day
64-17-5	ethanol, ethyl alcohol			
Worker DNEL	long-term	inhalation	systemic	950 mg/m³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
5131-66-8	3-butoxypropan-2-ol; propylene glycol monobutyl ether	
Freshwater		0,525 mg/l
Freshwater	(intermittent releases)	5,25 mg/l
Marine wate	r	0,052 mg/l
Freshwater	sediment	2,36 mg/kg
Marine sedir	nent	0,236 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,16 mg/kg
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Freshwater	(intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. After cleaning apply high-fat content skin care cream.



ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 5 of 10

Eye/face protection

Eye protection: not required.

Hand protection Hand protection is not required

Skin protection

Body protection: not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and che Physical state: Colour: Odour:	emical properties Liquid colourless cloudy fruity	
pH-Value (at 20 °C):		6,0 - 8,0 neutral
Changes in the physical state Melting point: Initial boiling point and boiling range:		not determined 100 °C
Flash point:		>70 °C
Flammability Solid: Gas:		not applicable not applicable
Explosive properties The product is not: Explosive.		
Lower explosion limits: Upper explosion limits:		not applicable not applicable
Ignition temperature:		not applicable
Auto-ignition temperature Solid: Gas: Decomposition temperature:		not applicable not applicable not determined
Oxidizing properties Not oxidising.		
Vapour pressure: (at 20 °C)		23,5 hPa
Density (at 20 °C):		0,99 g/cm³
Water solubility: Solubility in other solvents		completely miscible
not determined		
Partition coefficient:		not determined
Vapour density:		not determined
Evaporation rate:		not determined
Solvent content:		8 %
9.2. Other information Solid content:		not determined

SECTION 10: Stability and reactivity



ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 6 of 10

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Oxidising agent, strong

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
5131-66-8	66-8 3-butoxypropan-2-ol; propylene glycol monobutyl ether						
	oral	LD50 mg/kg	3300	Rat	Study report (1987)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1987)	OECD Guideline 402	
64-17-5	ethanol, ethyl alcohol						
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401	
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. After cleaning apply high-fat content skin care cream.

Practical experience

Observations relevant to classification

Has degreasing effect on the skin. After cleaning apply high-fat content skin care cream.



according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 7 of 10

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
5131-66-8	3-butoxypropan-2-ol; prop	ylene glycol i	monobutyl	ether			
	Acute fish toxicity	LC50 1000 mg/l	> 560 - <	96 h	Poecilia reticulata	Study report (1987)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Pseudokirchneriella subcapitata	Study report (1987)	Method: other: No specific guidance cite
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1987)	OECD Guideline 202
	Acute bacteria toxicity	(> 1000 m	g/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (2009)	OECD Guideline 209
64-17-5	ethanol, ethyl alcohol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	> 79	100 d	Oryzias latipes	Environmental Toxicology and Chemistry,	Chronic effects of substance on reproduc
	Algea toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	o Chemical name			Log Pow	
5131-66-8	3-butoxypropan-2-ol; propylene glycol monol	3-butoxypropan-2-ol; propylene glycol monobutyl ether			1,2
64-17-5	ethanol, ethyl alcohol		-0,77		
BCF					
CASNO	Chamical name	PCE	Spacios	Source	

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol, ethyl alcohol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.



ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 8 of 10

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No special measures are necessary.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Water with tenside additive.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport) No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Keep container tightly closed.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant



according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 9 of 10

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 3-butoxypropan-2-ol; propylene glycol monobutyl ether Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation).

National regulatory information

1 - slightly hazardous to water

Water hazard class (D): Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations** DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds



according to Regulation (EC) No 1907/2006

ORAFOL® Long-Lasting Seal for Matt Car Wrapping Films

Revision date: 18.09.2020

Product code: 359500027

Page 10 of 10

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
EUH210	Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)